

I. Amendments to the Claims

1. (Currently Amended): A method for constructing an illuminating and reflecting apparatus, said method comprising the steps of:

providing a layered metal substrate with an aluminum metal layer positioned between a first and a second copper layer;

removing ~~at least~~ a defined area of said at least one copper layer to form a reflective portion within said area; and

providing a localized light source positioned to allow light to reflect off of said reflective portion.

2. (Currently Amended): The method of claim 1, further comprising the step of removing an area of said aluminum metal layer such that a non-planar surface is formed in said aluminum metal layer.

3. (Original): The method of claim 2, further comprising the step of removing a defined area of at least one copper layer such that an opening is defined in said layered metal substrate.

4. (Original): The method of claim 3, further comprising the step of coating said reflective portion with a substance to provide specific reflectivity levels.

5. (Original): The method of claim 3, further comprising the step of providing a transparent substrate positioned on said first copper layer.

6. (Original): The method of claim 3, further comprising the step of providing a reflective substrate positioned on said second copper layer.

BRINKS  
HOFER  
GILSON  
LIONE

BRINKS HOFER GILSON & LIONE  
PO Box 10395  
Chicago, IL 60610

7. (Currently Amended): A method for forming a reflective aperture in a circuit board for providing illumination in automotive applications, said method comprising the steps of:

providing a layered metal substrate[[:]] having a top metal layer, a middle metal layer, and a bottom metal layer;

removing at least a top metal layer of said layered metal substrate to form a reflective area; and

providing a localized light source positioned so as to allow light to reflect off of said reflective area.

8. (Currently Amended): The method of claim 7, further comprising the step of defining a non-planar aperture in the middle metal layer of said layered metal substrate.

9. (Currently Amended): The method of claim 8, further comprising the step of defining an aperture in the bottom metal layer of said layered metal substrate aligned with said non-planar aperture in said middle layer.

10. (Currently Amended): A method for forming a reflective aperture in a circuit board for providing illumination in automotive applications, said method comprising the steps of:

providing a layered metal substrate[[:]] having a top metal layer, a middle metal layer, and a bottom metal layer;

applying a layer of masking material on a surface of ~~at least one a~~ top metal layer of said layered metal substrate;

exposing said layered metal substrate to an etching process;

removing said masking material from said ~~at least one~~ top metal layer of said layered metal substrate to expose reflective areas of said ~~at least one layer~~ layered metal substrate; and

BRINKS  
HOFFER  
GILSON  
& LIONE

BRINKS HOFER GILSON & LIONE  
PO Box 10395  
Chicago, IL 60610

providing a localized light source positioned so as to allow light to reflect off of said reflective area.

11. (Currently Amended): The method of claim 10, further comprising the steps of:

applying a layer of masking material on a surface of an aluminum metal layer;

exposing said layered metal substrate to an aluminum etching process; and

removing said masking material from said aluminum metal layer.

12. (Previously Presented): The method of claim 10, further comprising the step of defining a non-planar aperture in the ~~at least one~~ middle metal layer of said layered metal substrate.

13. (Previously Presented): The method of claim 12, further comprising the step of defining an aperture in a bottom layer of said layered metal substrate aligned with said non-planar aperture in said ~~at least one~~ middle metal layer.

14. (Currently Amended): A reflective circuit board comprising:  
a substrate comprised of a layer of aluminum metal layer positioned between two layers of copper;  
at least one exposed area of reflective aluminum; and  
a localized light source positioned to provide illumination of said exposed aluminum.

15. (Currently Amended): The reflective circuit board of claim 14, further comprising a non-planar aperture defined in said aluminum metal layer.



BRINKS HOFER GILSON & LIONE  
PO Box 10395  
Chicago, IL 60610

16. (Original): The reflective circuit board of claim 15, further comprising an aperture defined through all of said layers of said substrate.

17. (Currently Amended): The reflective circuit board of claim 15, further comprising a reflective coating on said non-planar surfaces of said aluminum metal layer.

18. (Original): The reflective circuit board of claim 16, wherein said localized light source is substantially aligned with said aperture.

19. (Original): The reflective circuit board of claim 18, further comprising a layer of reflective substrate over said aperture opposite said localized light source.

20. (Currently Amended): The reflective circuit board of claim 14, further comprising a layer of transparent substrate over said at least one layer of exposed area of reflective aluminum.

21. (New): The method of claim 1, further comprising the step of removing an area of said aluminum metal layer such that a non-planar surface is formed in said aluminum metal layer, after removing the defined area.

22. (New): The method of claim 7, further comprising the step of defining a non-planar aperture in the middle metal layer of said layered metal substrate, after removing the at least top metal layer.

23. (New): The method of claim 10, further comprising the step of defining a non-planar aperture in the at least one layer of said layered metal substrate, after exposing said layered metal substrate to an etching process.



BRINKS HOFER GILSON & LIONE  
PO Box 10395  
Chicago, IL 60610